



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : Explosion Proof - High Efficiency

Frame : 184T
Output : 1.5 HP
Frequency : 60 Hz
Poles : 8
Full load speed : 860 rpm
Slip : 4.44 %
Voltage : 208-230/460 V
Rated current : 6.00-5.43/2.71 A
Locked rotor current : 29.8/14.9 A
Locked rotor current (I_L/I_n) : 5.5
No-load current : 3.63/1.81 A
Full load torque : 9.04 lb.ft
Locked rotor torque : 250 %
Breakdown torque : 260 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 32 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP54
Approximate weight : 122 lb
Moment of inertia : 0.44375 sq.ft.lb
Noise level : 50 dB(A)

	D.E.	N.D.E.
Bearings	6307 2RS	6206 2RS
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.66	77.0
75%	0.58	75.5
50%	0.47	74.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #00159XP3E184T

Performed by

Checked