



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : W22 High Efficiency

Frame : 213/5T  
 Output : 2 HP  
 Frequency : 60 Hz  
 Poles : 8  
 Full load speed : 870 rpm  
 Slip : 3.33 %  
 Voltage : 208-230/460 V  
 Rated current : 7.65-6.92/3.46 A  
 Locked rotor current : 45.7/22.8 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.6  
 No-load current : 4.40/2.20 A  
 Full load torque : 11.9 lb.ft  
 Locked rotor torque : 240 %  
 Breakdown torque : 290 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 43 s (hot)  
 Service factor : 1.25  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 141 lb  
 Moment of inertia : 1.1910 sq.ft.lb  
 Noise level : 52 dB(A)

	D.E.	N.D.E.
Bearings	6308 ZZ	6207 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.66	82.5
75%	0.53	81.5
50%	0.47	78.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #00209EP3E213T-W22

Performed by

Checked