



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 High Efficiency

Frame : 213/5T
Output : 2 HP
Frequency : 60 Hz
Poles : 8
Full load speed : 870 rpm
Slip : 3.33 %
Voltage : 575 V
Rated current : 2.77 A
Locked rotor current : 18.3 A
Locked rotor current (I_L/I_n) : 6.6
No-load current : 1.76 A
Full load torque : 11.9 lb.ft
Locked rotor torque : 240 %
Breakdown torque : 290 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 43 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 141 lb
Moment of inertia : 1.1910 sq.ft.lb
Noise level : 52 dB(A)

| | D.E. | N.D.E. |
|---------------------|---------|---------|
| Bearings | 6308 ZZ | 6207 ZZ |
| Regreasing interval | --- | --- |
| Grease amount | --- | --- |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.66 | 82.5 |
| 75% | 0.53 | 81.5 |
| 50% | 0.47 | 78.5 |

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #00209EP3H213T-W22

Performed by

Checked