



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : IEC Tru-Metric - TEFC (IP55) - Aluminum Frame

Frame : 132S
 Output : 3 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 875 rpm
 Slip : 2.78 %
 Voltage : 460 V
 Rated current : 4.70 A
 Locked rotor current : 34.8 A
 Locked rotor current (I_L/I_n) : 7.4
 No-load current : 2.80 A
 Full load torque : 17.8 lb.ft
 Locked rotor torque : 250 %
 Breakdown torque : 270 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 20 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 135 lb
 Moment of inertia : 1.7862 sq.ft.lb
 Noise level : 52 dB(A)

	D.E.	N.D.E.
Bearings	6308 ZZ	6207 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.70	84.0
75%	0.62	84.0
50%	0.50	82.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00209EP3YAL132S

Performed by

Checked