



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - TEFC - High Efficiency

Frame : 182/4T
 Output : 2 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1170 rpm
 Slip : 2.50 %
 Voltage : 208-230/460 V
 Rated current : 6.97-6.30/3.15 A
 Locked rotor current : 52.9/26.5 A
 Locked rotor current (I_L/I_n) : 8.4
 No-load current : 4.18/2.09 A
 Full load torque : 8.86 lb.ft
 Locked rotor torque : 260 %
 Breakdown torque : 370 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 20 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 80 lb
 Moment of inertia : 0.56572 sq.ft.lb
 Noise level : 52 dB(A)

	D.E.	N.D.E.
Bearings	6206 ZZ	6205 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.69	86.5
75%	0.60	85.5
50%	0.47	82.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00212EP3ER184TC-S

Performed by

Checked