



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 Super Premium

Frame : L143/5T
Output : 2 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1760 rpm
Slip : 2.22 %
Voltage : 208-230/460 V
Rated current : 5.26/2.63 A
Locked rotor current : 45.2/22.6 A
Locked rotor current (I_L/I_n) : 8.6
No-load current : 3.08/1.54 A
Full load torque : 5.89 lb.ft
Locked rotor torque : 290 %
Breakdown torque : 360 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 14 s (hot)
Service factor : 1.25 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 57 lb
Moment of inertia : 0.18153 sq.ft.lb
Noise level : 51 dB(A)

	D.E.	N.D.E.
Bearings	6205 ZZ	6204 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.81	88.5
75%	0.74	87.5
50%	0.61	86.5

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #00218EG3EL145T-W22

Performed by

Checked