



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JM" Type - TEFC - High Efficiency

Frame : 143/5JM
 Output : 2 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1755 rpm
 Slip : 2.50 %
 Voltage : 208-230/460 V
 Rated current : 6.52-5.90/2.95 A
 Locked rotor current : 44.3/22.1 A
 Locked rotor current (I_L/I_n) : 7.5
 No-load current : 3.72/1.86 A
 Full load torque : 5.90 lb.ft
 Locked rotor torque : 260 %
 Breakdown torque : 330 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 10 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 42 lb
 Moment of inertia : 0.14191 sq.ft.lb
 Noise level : 52 dB(A)

| | D.E. | N.D.E. | Load | Power factor | Efficiency (%) |
|---------------------|---------|---------|------|--------------|----------------|
| Bearings | 6206 ZZ | 6203 ZZ | 100% | 0.76 | 84.0 |
| Regreasing interval | --- | --- | 75% | 0.67 | 84.0 |
| Grease amount | --- | --- | 50% | 0.53 | 81.5 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00218EP3E145JM-S

Performed by

Checked