



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Three-Phase : NEMA 56 Frames - TEFC

Frame : F56H  
Output : 2 HP  
Frequency : 60 Hz  
Poles : 4  
Full load speed : 1740 rpm  
Slip : 3.33 %  
Voltage : 208-230/460 V  
Rated current : 6.15-5.80/2.90 A  
Locked rotor current : 49.9/24.9 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 8.6  
No-load current : 3.40/1.70 A  
Full load torque : 5.96 lb.ft  
Locked rotor torque : 300 %  
Breakdown torque : 320 %  
Design : A  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 10 s (hot)  
Service factor : 1.15 (1.00 at 208V)  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 45 lb  
Moment of inertia : 0.20408 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.79	82.0
75%	0.71	81.0
50%	0.59	77.5

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #00218ES3EF56

Performed by

Checked