



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : G56H  
Output : 2 HP  
Frequency : 60 Hz  
Poles : 4  
Full load speed : 1730 rpm  
Slip : 3.89 %  
Voltage : 115/208-230 V  
Rated current : 28.0/14.0-14.0 A  
Locked rotor current : 157/78.4 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 5.6  
No-load current : 21.2/10.6 A  
Full load torque : 5.99 lb.ft  
Locked rotor torque : 250 %  
Breakdown torque : 250 %  
Design : ---  
Insulation class : B  
Temperature rise : 80 K  
Locked rotor time : 6 s (hot)  
Service factor : 1.00 (1.00 at 208V)  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP21  
Approximate weight : 41 lb  
Moment of inertia : 0.23018 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.64	71.4
75%	0.53	70.6
50%	0.42	64.3

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #00218OS1BG56CFL

Performed by

Checked