



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : 56H
 Output : 2 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3475 rpm
 Slip : 3.47 %
 Voltage : 208-230/460 V
 Rated current : 5.79-5.24/2.62 A
 Locked rotor current : 40.3/20.2 A
 Locked rotor current (I_L/I_n) : 7.7
 No-load current : 2.07/1.04 A
 Full load torque : 2.98 lb.ft
 Locked rotor torque : 230 %
 Breakdown torque : 290 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 11 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 31 lb
 Moment of inertia : 0.09634 sq.ft.lb
 Noise level : 68 dB(A)

	D.E.	N.D.E.
Bearings	6204 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.90	80.0
75%	0.86	78.5
50%	0.76	75.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00236ES3E56-S

Performed by

Checked