



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : F56H
Output : 2 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3525 rpm
Slip : 2.08 %
Voltage : 115/208-230 V
Rated current : 21.9/11.3-11.0 A
Locked rotor current : 175/87.6 A
Locked rotor current (I_L/I_n) : 8.0
No-load current : 14.0/7.00 A
Full load torque : 2.94 lb.ft
Locked rotor torque : 250 %
Breakdown torque : 280 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 42 lb
Moment of inertia : 0.06644 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6204 ZZ	6203 ZZ	100%	0.75	77.9
Regreasing interval	---	---	75%	0.67	76.2
Grease amount	---	---	50%	0.59	71.1

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #00236OS1BF56C

Performed by

Checked