



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Jet Pump - NEMA 56 : Single-Phase - Threaded - ODP (IP21)

Frame : E56
 Output : 2 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3490 rpm
 Slip : 3.06 %
 Voltage : 115/208-230 V
 Rated current : 20.7/11.1-10.4 A
 Locked rotor current : 145/72.4 A
 Locked rotor current (I_L/I_n) : 7.0
 No-load current : 11.3/5.65 A
 Full load torque : 2.97 lb.ft
 Locked rotor torque : 250 %
 Breakdown torque : 250 %
 Design : ---
 Insulation class : B
 Temperature rise : 80 K
 Locked rotor time : 6 s (hot)
 Service factor : 1.20 (1.00 at 208V)
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP21
 Approximate weight : 44 lb
 Moment of inertia : 0.05553 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 2RS	6203 2RS	100%	0.80	77.3
Regreasing interval	---	---	75%	0.73	77.0
Grease amount	---	---	50%	0.62	72.8

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00236OS1BJP56J

Performed by

Checked