



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Single-Phase: Fractional Explosion Proof Motors

Frame : 56H
 Output : 2 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3450 rpm
 Slip : 4.17 %
 Voltage : 230 V
 Rated current : 9.80 A
 Locked rotor current : 63.7 A
 Locked rotor current (I_L/I_n) : 6.5
 No-load current : 4.40 A
 Full load torque : 3.00 lb.ft
 Locked rotor torque : 120 %
 Breakdown torque : 250 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 4 s (hot)
 Service factor : 1.00
 Duty cycle : S1
 Ambient temperature : -20°C - +50°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 40 lb
 Moment of inertia : 0.02254 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6205 ZZ	6203 ZZ	100%	0.85	78.1
Regreasing interval	---	---	75%	0.80	77.0
Grease amount	---	---	50%	0.70	74.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00236XS1C56H

Performed by

Checked