



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: Fractional Explosion Proof Motors

Frame : 56H
 Output : 2 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3450 rpm
 Slip : 4.17 %
 Voltage : 208-230/460 V
 Rated current : 5.97-5.40/2.70 A
 Locked rotor current : 38.3/19.2 A
 Locked rotor current (I_L/I_n) : 7.1
 No-load current : 2.20/1.10 A
 Full load torque : 3.00 lb.ft
 Locked rotor torque : 320 %
 Breakdown torque : 370 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 3 s (hot)
 Service factor : 1.00
 Duty cycle : S1
 Ambient temperature : -20°C - +50°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 32 lb
 Moment of inertia : 0.01495 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6203 ZZ	100%	0.84	83.0
Regreasing interval	---	---	75%	0.79	83.0
Grease amount	---	---	50%	0.75	76.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00236XS3E56H

Performed by

Checked