



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 High Efficiency

Frame : 213/5T
 Output : 3 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 865 rpm
 Slip : 3.89 %
 Voltage : 208-230/460 V
 Rated current : 9.58-8.66/4.33 A
 Locked rotor current : 61.5/30.7 A
 Locked rotor current (I_L/I_n) : 7.1
 No-load current : 4.60/2.30 A
 Full load torque : 18.0 lb.ft
 Locked rotor torque : 200 %
 Breakdown torque : 210 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 30 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 159 lb
 Moment of inertia : 2.0244 sq.ft.lb
 Noise level : 52 dB(A)

	D.E.	N.D.E.
Bearings	6308 ZZ	6207 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.76	84.0
75%	0.70	84.0
50%	0.59	82.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00309EP3E215T-W22

Performed by

Checked