



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Single-Phase : W21 TEFC (IP55)

Frame : W213/5T  
Output : 3 HP  
Frequency : 60 Hz  
Poles : 6  
Full load speed : 1160 rpm  
Slip : 3.33 %  
Voltage : 208-230/460 V  
Rated current : 14.8-13.4/6.70 A  
Locked rotor current : 80.4/40.2 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.0  
No-load current : 4.80/2.40 A  
Full load torque : 13.4 lb.ft  
Locked rotor torque : 200 %  
Breakdown torque : 200 %  
Design : ---  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 6 s (hot)  
Service factor : 1.15  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 126 lb  
Moment of inertia : 0.60986 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6308 ZZ	6206 ZZ	100%	0.92	80.0
Regreasing interval	---	---	75%	0.91	79.0
Grease amount	---	---	50%	0.87	74.0

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #00312ES1E215T

Performed by

Checked