



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JM" Type - ODP - NEMA Premium Efficiency

Frame : 213/5JM
 Output : 3 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1175 rpm
 Slip : 2.08 %
 Voltage : 208-230/460 V
 Rated current : 9.20-8.32/4.16 A
 Locked rotor current : 49.1/24.5 A
 Locked rotor current (I_L/I_n) : 5.9
 No-load current : 4.58/2.29 A
 Full load torque : 13.2 lb.ft
 Locked rotor torque : 210 %
 Breakdown torque : 260 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 39 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : ODP
 Approximate weight : 98 lb
 Moment of inertia : 0.81038 sq.ft.lb
 Noise level : 55 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6209 ZZ	6206 ZZ	100%	0.75	88.5
Regreasing interval	---	---	75%	0.68	87.5
Grease amount	---	---	50%	0.56	86.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00312OT3E213JMV-S

Performed by

Checked