



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : ODP – Open Induction Motors – NEMA Premium Efficiency

Frame : 213/5T
 Output : 3 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1170 rpm
 Slip : 2.50 %
 Voltage : 208-230/460 V
 Rated current : 9.44-8.54/4.27 A
 Locked rotor current : 51.2/25.6 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 5.00/2.50 A
 Full load torque : 13.3 lb.ft
 Locked rotor torque : 160 %
 Breakdown torque : 260 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 25 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP21
 Approximate weight : 66 lb
 Moment of inertia : 0.82794 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.
Bearings	6208 ZZ	6206 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.73	88.5
75%	0.65	87.5
50%	0.52	85.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00312OT3E213T

Performed by

Checked