



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : P-Base Motors : High Efficiency

Frame : 182HP
 Output : 3 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1760 rpm
 Slip : 2.22 %
 Voltage : 230/460 V
 Rated current : 8.10/4.05 A
 Locked rotor current : 60.8/30.4 A
 Locked rotor current (I_L/I_n) : 7.5
 No-load current : 4.40/2.20 A
 Full load torque : 8.83 lb.ft
 Locked rotor torque : 230 %
 Breakdown torque : 320 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 25 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 92 lb
 Moment of inertia : 0.27717 sq.ft.lb
 Noise level : 56 dB(A)

| | D.E. | N.D.E. |
|---------------------|---------|---------|
| Bearings | 6308 ZZ | 6206 ZZ |
| Regreasing interval | --- | --- |
| Grease amount | --- | --- |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.78 | 87.5 |
| 75% | 0.71 | 87.5 |
| 50% | 0.59 | 85.5 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00318EP3E182HP

Performed by

Checked