



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump : Three-Phase - "JM" Type - ODP - High Efficiency

Frame : F143/5JM
 Output : 3 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3400 rpm
 Slip : 5.56 %
 Voltage : 575 V
 Rated current : 2.92 A
 Locked rotor current : 24.8 A
 Locked rotor current (I_L/I_n) : 8.5
 No-load current : 0.960 A
 Full load torque : 4.57 lb.ft
 Locked rotor torque : 400 %
 Breakdown torque : 300 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 15 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP21
 Approximate weight : 46 lb
 Moment of inertia : 0.07119 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6206 ZZ	6204 ZZ	100%	0.92	85.5
Regreasing interval	---	---	75%	0.88	84.0
Grease amount	---	---	50%	0.80	81.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00336OP3H145JM

Performed by

Checked