



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Close Coupled Pump : Three-Phase - "JP" Type - ODP - High Efficiency

Frame : F143/5JP  
 Output : 3 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3400 rpm  
 Slip : 5.56 %  
 Voltage : 200/400 V  
 Rated current : 8.40/4.20 A  
 Locked rotor current : 71.4/35.7 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 8.5  
 No-load current : 2.76/1.38 A  
 Full load torque : 4.57 lb.ft  
 Locked rotor torque : 400 %  
 Breakdown torque : 300 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 15 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP21  
 Approximate weight : 46 lb  
 Moment of inertia : 0.07119 sq.ft.lb  
 Noise level : ---

	D.E.	N.D.E.
Bearings	6206 ZZ	6204 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.92	85.5
75%	0.88	84.0
50%	0.80	81.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #00336OP3V145JP

Performed by

Checked