



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Compressor Duty : Single-Phase - ODP

Frame : F56H  
Output : 3 HP  
Frequency : 60 Hz  
Poles : 2  
Full load speed : 3440 rpm  
Slip : 4.44 %  
Voltage : 115/208-230 V  
Rated current : 29.4/16.2-14.7 A  
Locked rotor current : 176/88.2 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.0  
No-load current : 13.0/6.50 A  
Full load torque : 4.52 lb.ft  
Locked rotor torque : 180 %  
Breakdown torque : 190 %  
Design : ---  
Insulation class : B  
Temperature rise : 80 K  
Locked rotor time : 6 s (hot)  
Service factor : 1.00 (1.00 at 208V)  
Duty cycle : COMPRESSOR  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP21  
Approximate weight : 42 lb  
Moment of inertia : 0.06644 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.86	77.0
75%	0.80	77.0
50%	0.70	76.0

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #00336OS1BCDF56

Performed by

Checked