



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : ODP (IP22)

Frame : 182T
Output : 3 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3520 rpm
Slip : 2.22 %
Voltage : 230 V
Rated current : 15.0 A
Locked rotor current : 96.0 A
Locked rotor current (I_L/I_n) : 6.4
No-load current : 8.50 A
Full load torque : 4.42 lb.ft
Locked rotor torque : 230 %
Breakdown torque : 260 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP22
Approximate weight : 82 lb
Moment of inertia : 0.18035 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6206 ZZ	6205 ZZ	100%	0.79	81.5
Regreasing interval	---	---	75%	0.71	81.0
Grease amount	---	---	50%	0.60	78.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #00336OS1D182T

Performed by

Checked