



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Jet Pump: Three-Phase - W01 (Rolled Steel) - Threaded - ODP - Standard
 Efficiency

Frame : 56HJ
 Output : 3 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3450 rpm
 Slip : 4.17 %
 Voltage : 208-230/460 V
 Rated current : 8.60-7.78/3.89 A
 Locked rotor current : 54.5/27.2 A
 Locked rotor current (I_L/I_n) : 7.0
 No-load current : 3.20/1.60 A
 Full load torque : 4.51 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 250 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 8 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : ODP
 Approximate weight : 30 lb
 Moment of inertia : 0.09587 sq.ft.lb
 Noise level : 62 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.87	81.5
Regreasing interval	---	---	75%	0.82	81.5
Grease amount	---	---	50%	0.70	80.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00336OS3EJPR56J-S

Performed by

Checked