



# Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three-Phase: W21 IE3 IEC Tru-Metric - TEFC (IP55) Multi-Mounting Aluminum Frame

Frame : 112M  
 Output : 5.5 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3505 rpm  
 Slip : 2.64 %  
 Voltage : 460 V  
 Rated current : 6.67 A  
 Locked rotor current : 57.4 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 8.6  
 No-load current : 2.30 A  
 Full load torque : 8.13 lb.ft  
 Locked rotor torque : 310 %  
 Breakdown torque : 440 %  
 Design : ---  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 24 s (hot)  
 Service factor : 1.25  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 79 lb  
 Moment of inertia : 0.18984 sq.ft.lb  
 Noise level : 64 dB(A)

	D.E.	N.D.E.
Bearings	6307 ZZ	6206 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.85	88.5
75%	0.79	87.5
50%	0.67	85.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #00436ET3YAL112M

Performed by

Checked