



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JP" Type - TEFC - NEMA Premium Efficiency

Frame : 213/5JP
 Output : 5 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1175 rpm
 Slip : 2.08 %
 Voltage : 208-230/460 V
 Rated current : 14.9-13.5/6.74 A
 Locked rotor current : 80.9/40.4 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 6.84/3.42 A
 Full load torque : 22.0 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 250 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 30 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 144 lb
 Moment of inertia : 1.2608 sq.ft.lb
 Noise level : 55 dB(A)

| | D.E. | N.D.E. | Load | Power factor | Efficiency (%) |
|---------------------|---------|---------|------|--------------|----------------|
| Bearings | 6209 ZZ | 6206 ZZ | 100% | 0.77 | 89.5 |
| Regreasing interval | --- | --- | 75% | 0.71 | 88.5 |
| Grease amount | --- | --- | 50% | 0.59 | 87.5 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00512ET3E215JP-S

Performed by

Checked