



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : P-Base Motors : High Efficiency

Frame : 184HP
 Output : 5 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1750 rpm
 Slip : 2.78 %
 Voltage : 230/460 V
 Rated current : 13.1/6.55 A
 Locked rotor current : 91.7/45.8 A
 Locked rotor current (I_L/I_n) : 7.0
 No-load current : 6.20/3.10 A
 Full load torque : 14.8 lb.ft
 Locked rotor torque : 210 %
 Breakdown torque : 300 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 18 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 102 lb
 Moment of inertia : 0.33886 sq.ft.lb
 Noise level : 56 dB(A)

	D.E.	N.D.E.
Bearings	6308 ZZ	6206 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.81	87.5
75%	0.75	87.5
50%	0.63	85.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00518EP3E184HP

Performed by

Checked