



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Farm Duty Motors : TEFC (IP55) - Single-Phase

Frame : W213/5TZ
Output : 5 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1730 rpm
Slip : 3.89 %
Voltage : 230 V
Rated current : 21.4 A
Locked rotor current : 171 A
Locked rotor current (I_L/I_n) : 8.0
No-load current : 8.40 A
Full load torque : 15.0 lb.ft
Locked rotor torque : 370 %
Breakdown torque : 270 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 126 lb
Moment of inertia : 0.43426 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6308 ZZ	6206 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.95	79.0
75%	0.92	78.0
50%	0.86	72.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #00518ES1DFD215Z

Performed by

Checked