



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump : Single-Phase - "JP" Type - TEFC - Standard Efficiency

Frame : 184JP
 Output : 5 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1730 rpm
 Slip : 3.89 %
 Voltage : 208-230/460 V
 Rated current : 22.5-21.4/10.7 A
 Locked rotor current : 171/85.6 A
 Locked rotor current (I_L/I_n) : 8.0
 No-load current : 9.00/4.50 A
 Full load torque : 15.0 lb.ft
 Locked rotor torque : 280 %
 Breakdown torque : 240 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 6 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 112 lb
 Moment of inertia : 0.43426 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.
Bearings	6307 ZZ	6206 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.95	79.0
75%	0.92	78.0
50%	0.86	72.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00518ES1E184JP

Performed by

Checked