



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

### DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : W01 (Rolled Steel) Close Coupled Pump TEFC - JM Type

Frame : 182/4JM  
Output : 5 HP  
Frequency : 60 Hz  
Poles : 2  
Full load speed : 3500 rpm  
Slip : 2.78 %  
Voltage : 208-230/460 V  
Rated current : 13.1-11.8/5.90 A  
Locked rotor current : 92.0/46.0 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.8  
No-load current : 4.40/2.20 A  
Full load torque : 7.40 lb.ft  
Locked rotor torque : 220 %  
Breakdown torque : 300 %  
Design : B  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 17 s (hot)  
Service factor : 1.15  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 78 lb  
Moment of inertia : 0.20787 sq.ft.lb  
Noise level : 68 dB(A)

	D.E.	N.D.E.
Bearings	6207 ZZ	6205 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.89	88.5
75%	0.85	88.5
50%	0.76	87.5

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #00536ET3E184JM-SG

Performed by

Checked