



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 IE2 IEC Tru-Metric - TEFC (IP55) Cast Iron Frame

Frame : 160L
 Output : 10 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 875 rpm
 Slip : 2.78 %
 Voltage : 460 V
 Rated current : 15.6 A
 Locked rotor current : 81.1 A
 Locked rotor current (I_L/I_n) : 5.2
 No-load current : 9.30 A
 Full load torque : 59.2 lb.ft
 Locked rotor torque : 260 %
 Breakdown torque : 260 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 22 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 306 lb
 Moment of inertia : 3.4086 sq.ft.lb
 Noise level : 54 dB(A)

	D.E.	N.D.E.
Bearings	6309 C3	6209 C3
Regreasing interval	20000 h	20000 h
Grease amount	13 g	9 g

Load	Power factor	Efficiency (%)
100%	0.68	88.5
75%	0.59	87.5
50%	0.47	85.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00709EP3Y160L-W22

Performed by

Checked