



# Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

## DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Close Coupled Pump : Single-Phase - "JM" Type - TEFC - Standard Efficiency

Frame : 215JM  
 Output : 7.5 HP  
 Frequency : 60 Hz  
 Poles : 4  
 Full load speed : 1730 rpm  
 Slip : 3.89 %  
 Voltage : 208-230/460 V  
 Rated current : 35.5-34.0/17.0 A  
 Locked rotor current : 238/119 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.0  
 No-load current : 17.6/8.80 A  
 Full load torque : 22.5 lb.ft  
 Locked rotor torque : 320 %  
 Breakdown torque : 240 %  
 Design : ---  
 Insulation class : B  
 Temperature rise : 80 K  
 Locked rotor time : 6 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 157 lb  
 Moment of inertia : 0.88038 sq.ft.lb  
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6309 ZZ	6206 ZZ	100%	0.86	83.0
Regreasing interval	---	---	75%	0.81	82.0
Grease amount	---	---	50%	0.71	78.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #00718ES1E215JM

Performed by

Checked