



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : W21 TEFC (IP55)

Frame : 215TZ
Output : 7.5 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1730 rpm
Slip : 3.89 %
Voltage : 208-230/460 V
Rated current : 35.5-34.0/17.0 A
Locked rotor current : 238/119 A
Locked rotor current (I_L/I_n) : 7.0
No-load current : 19.2/9.60 A
Full load torque : 22.5 lb.ft
Locked rotor torque : 320 %
Breakdown torque : 240 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 158 lb
Moment of inertia : 0.88038 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6308 ZZ	6206 ZZ	100%	0.86	83.0
Regreasing interval	---	---	75%	0.81	82.0
Grease amount	---	---	50%	0.71	78.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #00718ES1E215TZ

Performed by

Checked