



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : P-Base Motors : High Efficiency

Frame : 184HP
 Output : 7.5 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3460 rpm
 Slip : 3.89 %
 Voltage : 230/460 V
 Rated current : 17.5/8.76 A
 Locked rotor current : 123/61.3 A
 Locked rotor current (I_L/I_n) : 7.0
 No-load current : 5.55/2.78 A
 Full load torque : 11.2 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 230 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 15 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 108 lb
 Moment of inertia : 0.23611 sq.ft.lb
 Noise level : 69 dB(A)

	D.E.	N.D.E.
Bearings	6308 ZZ	6206 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.87	88.5
75%	0.85	87.5
50%	0.79	85.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00736EP3E184HP

Performed by

Checked