



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Close Coupled Pump: Three-Phase - W22 "JM" Type - TEFC - High Efficiency

Frame : 182/4JM
Output : 7.5 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3470 rpm
Slip : 3.61 %
Voltage : 575 V
Rated current : 6.78 A
Locked rotor current : 48.8 A
Locked rotor current (I_L/I_n) : 7.2
No-load current : 2.52 A
Full load torque : 11.2 lb.ft
Locked rotor torque : 220 %
Breakdown torque : 290 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 16 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 93 lb
Moment of inertia : 0.22876 sq.ft.lb
Noise level : 69 dB(A)

	D.E.	N.D.E.
Bearings	6307 ZZ	6206 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.90	88.5
75%	0.88	88.5
50%	0.83	87.5

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #00736EP3H184JM-W22

Performed by

Checked