



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Saw Arbor Motors : Single and Double Shaft End

Frame : 80L
 Output : 7.5 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3490 rpm
 Slip : 3.06 %
 Voltage : 575 V
 Rated current : 7.81 A
 Locked rotor current : 71.8 A
 Locked rotor current (I_L/I_n) : 9.2
 No-load current : 3.52 A
 Full load torque : 11.1 lb.ft
 Locked rotor torque : 400 %
 Breakdown torque : 460 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 5 s (hot)
 Service factor : 1.15
 Duty cycle : S6 50%
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP54
 Approximate weight : 120 lb
 Moment of inertia : 0.14357 sq.ft.lb
 Noise level : 62 dB(A)

	D.E.	N.D.E.
Bearings	6307 ZZ	6207 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.81	87.4
75%	0.75	87.0
50%	0.64	85.2

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00736ES3HSA80LR

Performed by

Checked