



# Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JP" Type - TEFC - NEMA Premium Efficiency

Frame : 213/5JP  
 Output : 7.5 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3530 rpm  
 Slip : 1.94 %  
 Voltage : 208-230/460 V  
 Rated current : 19.2-17.3/8.67 A  
 Locked rotor current : 132/65.9 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.6  
 No-load current : 6.63/3.32 A  
 Full load torque : 11.0 lb.ft  
 Locked rotor torque : 260 %  
 Breakdown torque : 300 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 15 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 133 lb  
 Moment of inertia : 0.54959 sq.ft.lb  
 Noise level : 70 dB(A)

|                     | D.E.    | N.D.E.  | Load | Power factor | Efficiency (%) |
|---------------------|---------|---------|------|--------------|----------------|
| Bearings            | 6209 ZZ | 6206 ZZ | 100% | 0.89         | 89.5           |
| Regreasing interval | ---     | ---     | 75%  | 0.85         | 88.5           |
| Grease amount       | ---     | ---     | 50%  | 0.76         | 87.5           |

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #00736ET3E213JP-S

Performed by

Checked