



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : ODP (IP22)

Frame : 184T
Output : 7.5 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3510 rpm
Slip : 2.50 %
Voltage : 208-230 V
Rated current : 33.4-30.0 A
Locked rotor current : 216 A
Locked rotor current (I_L/I_n) : 7.2
No-load current : 7.10 A
Full load torque : 11.1 lb.ft
Locked rotor torque : 240 %
Breakdown torque : 230 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP22
Approximate weight : 115 lb
Moment of inertia : 0.29425 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6206 ZZ	6205 ZZ	100%	0.95	85.0
Regreasing interval	---	---	75%	0.93	84.0
Grease amount	---	---	50%	0.90	82.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #00736OS1C184T

Performed by

Checked