



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : W22 Oil Well Pumping : High Slip - NEMA Design "D" - TEFC (IP55)

Frame : 254/6T
 Output : 10 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1105 rpm
 Slip : 7.92 %
 Voltage : 208-230/460 V
 Rated current : 28.6-25.4/12.7 A
 Locked rotor current : 155/77.5 A
 Locked rotor current (I_L/I_n) : 6.1
 No-load current : 7.60/3.80 A
 Full load torque : 46.9 lb.ft
 Locked rotor torque : 320 %
 Breakdown torque : 0 %
 Design : D
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 16 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 298 lb
 Moment of inertia : 4.3742 sq.ft.lb
 Noise level : 59 dB(A)

	D.E.	N.D.E.
Bearings	6309 C3	6209 C3
Regreasing interval	20000 h	20000 h
Grease amount	13 g	9 g

Load	Power factor	Efficiency (%)
100%	0.90	82.5
75%	0.88	84.0
50%	0.80	82.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #01012ES3EOW256T-W22

Performed by

Checked