



# Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

## DATA SHEET

### Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three Phase: W01 (Rolled Steel) - ODP - NEMA Premium Efficiency

Frame : 254/6T  
 Output : 10 HP  
 Frequency : 60 Hz  
 Poles : 6  
 Full load speed : 1180 rpm  
 Slip : 1.67 %  
 Voltage : 208-230/460 V  
 Rated current : 30.7-27.8/13.9 A  
 Locked rotor current : 147/73.7 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 5.3  
 No-load current : 14.7/7.33 A  
 Full load torque : 43.9 lb.ft  
 Locked rotor torque : 210 %  
 Breakdown torque : 230 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 34 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : ODP  
 Approximate weight : 209 lb  
 Moment of inertia : 2.4985 sq.ft.lb  
 Noise level : 59 dB(A)

	D.E.	N.D.E.
Bearings	6309 Z-C3	6208 Z-C3
Regreasing interval	20000 h	20000 h
Grease amount	13 g	8 g

Load	Power factor	Efficiency (%)
100%	0.74	91.7
75%	0.68	91.7
50%	0.56	91.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #01012OT3E256T-S

Performed by

Checked