



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JP" Type - TEFC - High Efficiency

Frame : 213/5JP
 Output : 10 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1755 rpm
 Slip : 2.50 %
 Voltage : 208-230/460 V
 Rated current : 26.8-24.2/12.1 A
 Locked rotor current : 165/82.3 A
 Locked rotor current (I_L/I_n) : 6.8
 No-load current : 9.78/4.89 A
 Full load torque : 29.5 lb.ft
 Locked rotor torque : 210 %
 Breakdown torque : 260 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 8 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 140 lb
 Moment of inertia : 1.2916 sq.ft.lb
 Noise level : 60 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6209 ZZ	6206 ZZ	100%	0.87	89.5
Regreasing interval	---	---	75%	0.82	89.5
Grease amount	---	---	50%	0.72	89.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #01018EP3E215JP-S

Performed by

Checked