



# Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

## DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Close Coupled Pump : Single-Phase - "JM" Type - TEFC - Standard Efficiency

Frame : 215JM  
Output : 10 HP  
Frequency : 60 Hz  
Poles : 4  
Full load speed : 1740 rpm  
Slip : 3.33 %  
Voltage : 208-230/460 V  
Rated current : 44.8-40.5/20.3 A  
Locked rotor current : 271/136 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.7  
No-load current : 12.2/6.10 A  
Full load torque : 29.8 lb.ft  
Locked rotor torque : 260 %  
Breakdown torque : 240 %  
Design : ---  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 6 s (hot)  
Service factor : 1.15  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 181 lb  
Moment of inertia : 1.1533 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6309 ZZ	6206 ZZ	100%	0.97	83.0
Regreasing interval	---	---	75%	0.96	82.0
Grease amount	---	---	50%	0.94	80.0

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #01018ES1E215JM

Performed by

Checked