



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : W21 TEFC (IP55)

Frame : 215T
Output : 10 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1740 rpm
Slip : 3.33 %
Voltage : 208-230/460 V
Rated current : 44.8-40.5/20.3 A
Locked rotor current : 271/136 A
Locked rotor current (I_L/I_n) : 6.7
No-load current : 12.2/6.10 A
Full load torque : 29.8 lb.ft
Locked rotor torque : 260 %
Breakdown torque : 240 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 181 lb
Moment of inertia : 1.1533 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6308 ZZ	6206 ZZ	100%	0.97	83.0
Regreasing interval	---	---	75%	0.96	82.0
Grease amount	---	---	50%	0.94	80.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #01018ES1E215T

Performed by

Checked