



# Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Saw Arbor Motors : Single and Double Shaft End

Frame : 90L  
 Output : 10 HP  
 Frequency : 60 Hz  
 Poles : 4  
 Full load speed : 1715 rpm  
 Slip : 4.72 %  
 Voltage : 208-230/460 V  
 Rated current : 32.5-29.4/14.7 A  
 Locked rotor current : 235/117 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 8.0  
 No-load current : 16.3/8.13 A  
 Full load torque : 30.2 lb.ft  
 Locked rotor torque : 400 %  
 Breakdown torque : 400 %  
 Design : ---  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 6 s (hot)  
 Service factor : 1.15  
 Duty cycle : S6 50%  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP54  
 Approximate weight : 178 lb  
 Moment of inertia : 0.39890 sq.ft.lb  
 Noise level : 51 dB(A)

	D.E.	N.D.E.
Bearings	6308 ZZ	6208 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.75	85.5
75%	0.67	85.5
50%	0.54	84.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #01018ES3ESA90LR

Performed by

Checked