



# Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

## DATA SHEET

### Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JM" Type - ODP - NEMA Premium Efficiency

Frame : 213/5JM  
 Output : 10 HP  
 Frequency : 60 Hz  
 Poles : 4  
 Full load speed : 1770 rpm  
 Slip : 1.67 %  
 Voltage : 575 V  
 Rated current : 9.92 A  
 Locked rotor current : 69.4 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.0  
 No-load current : 4.79 A  
 Full load torque : 29.3 lb.ft  
 Locked rotor torque : 250 %  
 Breakdown torque : 350 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 14 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : ODP  
 Approximate weight : 137 lb  
 Moment of inertia : 1.2952 sq.ft.lb  
 Noise level : 59 dB(A)

|                     | D.E.    | N.D.E.  | Load | Power factor | Efficiency (%) |
|---------------------|---------|---------|------|--------------|----------------|
| Bearings            | 6209 ZZ | 6206 ZZ | 100% | 0.83         | 91.7           |
| Regreasing interval | ---     | ---     | 75%  | 0.77         | 91.0           |
| Grease amount       | ---     | ---     | 50%  | 0.64         | 90.2           |

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #01018OT3H215JM-S

Performed by

Checked