



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Close Coupled Pump : Single-Phase - "JM" Type - TEFC - Standard Efficiency

Frame : 215JM
Output : 10 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3510 rpm
Slip : 2.50 %
Voltage : 208-230/460 V
Rated current : 43.2-38.8/19.4 A
Locked rotor current : 264/132 A
Locked rotor current (I_L/I_N) : 6.8
No-load current : 7.70/3.85 A
Full load torque : 14.8 lb.ft
Locked rotor torque : 220 %
Breakdown torque : 270 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 155 lb
Moment of inertia : 0.52847 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6309 ZZ	6206 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.95	86.0
75%	0.94	85.0
50%	0.91	83.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #01036ES1E215JM

Performed by

Checked