



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump : Single-Phase - "JP" Type - TEFC - Standard Efficiency

Frame : 215JP
 Output : 10 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3510 rpm
 Slip : 2.50 %
 Voltage : 208-230/460 V
 Rated current : 43.2-38.8/19.4 A
 Locked rotor current : 264/132 A
 Locked rotor current (I_L/I_n) : 6.8
 No-load current : 7.70/3.85 A
 Full load torque : 14.8 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 270 %
 Design : ---
 Insulation class : B
 Temperature rise : 80 K
 Locked rotor time : 6 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 155 lb
 Moment of inertia : 0.52847 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6309 ZZ	6206 ZZ	100%	0.95	86.0
Regreasing interval	---	---	75%	0.94	85.0
Grease amount	---	---	50%	0.91	83.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #01036ES1E215JP

Performed by

Checked