



# Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : W22 NEMA Premium - Ball Bearings

Frame : 213/5T  
Output : 10 HP  
Frequency : 60 Hz  
Poles : 2  
Full load speed : 3515 rpm  
Slip : 2.36 %  
Voltage : 208-230/460 V  
Rated current : 25.7-23.2/11.6 A  
Locked rotor current : 160/80.0 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.9  
No-load current : 6.00/3.00 A  
Full load torque : 14.7 lb.ft  
Locked rotor torque : 210 %  
Breakdown torque : 290 %  
Design : B  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 24 s (hot)  
Service factor : 1.25  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 163 lb  
Moment of inertia : 0.63620 sq.ft.lb  
Noise level : 72 dB(A)

	D.E.	N.D.E.
Bearings	6308 ZZ	6207 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.90	90.2
75%	0.87	90.2
50%	0.79	89.5

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #01036ET3E215TC-W22

Performed by

Checked