



Dealers Industrial Equipment

No.:

Date: 13-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - TEFC - NEMA Premium Efficiency

Frame : 213/5T
 Output : 10 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3530 rpm
 Slip : 1.94 %
 Voltage : 575 V
 Rated current : 9.20 A
 Locked rotor current : 69.0 A
 Locked rotor current (I_L/I_n) : 7.5
 No-load current : 3.01 A
 Full load torque : 14.7 lb.ft
 Locked rotor torque : 260 %
 Breakdown torque : 300 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 12 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 161 lb
 Moment of inertia : 0.71878 sq.ft.lb
 Noise level : 70 dB(A)

| | D.E. | N.D.E. |
|---------------------|---------|---------|
| Bearings | 6208 ZZ | 6206 ZZ |
| Regreasing interval | --- | --- |
| Grease amount | --- | --- |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.91 | 90.2 |
| 75% | 0.88 | 90.2 |
| 50% | 0.80 | 89.5 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #01036ET3H215T-S

Performed by

Checked