



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 NEMA Premium - Ball Bearings

Frame : 284/6T
Output : 15 HP
Frequency : 60 Hz
Poles : 8
Full load speed : 880 rpm
Slip : 2.22 %
Voltage : 575 V
Rated current : 15.5 A
Locked rotor current : 85.4 A
Locked rotor current (I_L/I_n) : 5.5
No-load current : 7.20 A
Full load torque : 88.3 lb.ft
Locked rotor torque : 200 %
Breakdown torque : 230 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 25 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 417 lb
Moment of inertia : 8.1809 sq.ft.lb
Noise level : 54 dB(A)

	D.E.	N.D.E.
Bearings	6311 C3	6211 C3
Regreasing interval	20000 h	20000 h
Grease amount	18 g	11 g

Load	Power factor	Efficiency (%)
100%	0.79	90.2
75%	0.73	91.0
50%	0.62	90.2

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #01509ET3H286T-W22

Performed by

Checked